



A1-13 3 Inputs Temperature Pod

Use this Pod to Monitor....

- Refrigerator Temperature
- Freezer Temperature

Features

Ambient Temperature Sensor

- Temperature Range: -40°C to +70°C
- Typical Accuracy at 25°C: $\pm 0.5^\circ\text{C}$
- Measurement Resolution: 0.0625°C

External Temperature Probe

- Temperature Range: -200°C to +200°C
- Typical Accuracy $\pm 1^\circ\text{C}$
- Measurement Resolution: 0.016°C
- Sensor Type: 3 x RTD

General Specifications

Physical Size

- 3.5 in x 3.25 in x 2in. (89mm x 83mm x 51mm)
- Weight: 8 oz. (227g)

Sampling Rate

- User Settable 30sec – 24hrs

Power Options

- 100-240Vac 50-60Hz
- DC Input 4-7Vdc
- 3 x AA Batteries (6 month life at 5 minute sampling intervals)

Emergency Data Storage

- 250 Samples per Sensor

Operating Environment

- -40°C to 70°C, 5-95%rh
Non-Condensing
When using Lithium batteries
With Alkaline batteries -20°C to 50°C

Wireless

- Range: 250ft Outdoors, 90ft Indoors
- Topology: Mesh
- Standard: IEEE 802.15.4
- Frequency: 2.4GHz DSS
- Power Output: -0.79dBm

Accessories

- E1-22 ISO 17025 NIST Traceable Calibration Certificate Available
- E1-16 External Battery Pack
- E1-19 Temperature Probes (RTD)
- E1-35 Thermal Buffer for use with E1-19 temperature probe
- E1-37 Combined Probe E1-19 and Buffer E1-35



CAS Data Loggers
8588 Mayfield Road, Chesterland, OH 44026
Tel: (800) 956-4437, Fax: (440) 729-2586
www.DataLoggerInc.com

Version 2.0 07/09/2009

SIMPLE TO USE « » SOPHISTICATED ANALYSIS « » SOUND INFORMATION