



B1-06 Direct Access Gateway

Features....

- Supports up to 16 Wireless Pods
- Fully Secure
- Internal Data Storage in Event of Internet Outage
- Intuitive easy to use Web Based Software (No Software Installation Necessary)
- Receive Alarms via Email, Text Message or Voice Notification
- Instant Access to Charts for Measurement History
- Download Data to a CSV File for Offline Analysis

General Specifications

Physical Size

- 6.75 in x 5.25 in x 1.5in. (172mm x 133mm x 38mm)
- Weight: 12 oz. (340g)

Power Options

- External 5Vdc 1A
- Power Over Ethernet

Wireless

- Range: 250ft outdoors, 90ft indoors
- Topology: Mesh
- Standard: IEEE 802.15.4
- Frequency: 2.4GHz DSS
- Power Output: -1dBm

Network

- DHCP or Static IP Address
- Standard Outbound http port 443 connection only
- No Firewall Configuration Necessary

Emergency Data Storage

- 1900 Measurements Readings

LEDs

- Diagnostic
 - Power
 - Wireless Status
 - Wireless Network Transmit
 - Error Status
 - Internet Transmission
 - Operational Status

Ports

- Ethernet 10BaseT/100BaseTX, RJ45
- USB

Security

- SSL Encryption
- User Account Password Protected, Limit Access to Certain Users

Operating Environment

- Operating Temperatures: 0°C to 50°C
- Operating Humidity: 10% to 90%rh Non-Condensing



CAS Data Loggers
8588 Mayfield Road, Chesterland, OH 44026
Tel: (800) 956-4437, Fax: (440) 729-2586
www.DataLoggerInc.com

Version 2.0 07/09/2009

SIMPLE TO USE « » SOPHISTICATED ANALYSIS « » SOUND INFORMATION